

ECHOFLEX

Coldplastic Type II

Roads & Highways
Excellent Durability
Sound Marking
Visibility by Night and Rainy Weather

ECHOFLEX - Coldplastic

BENEFITS

Product Characteristics

ECHOFLEX is profiled marking with sound effect, also called "rumble strip". ECHOFLEX is dedicated to high yield on road and Highways. Product is ready for use.

1 certification to attend road and urban needs:

Echoflex

3RHP1365b

1 000 000 wheel-overs (P5) & High night visibility (R4)

Main Performances

Extreme long lasting durability (P5)

Good visibility under rainy weather (RR2 & RW2)

Sound effect make it perfectly adapted to highways

Ease of maintenance by applying a paint layer

A marking material combining performance and sustainable development.

Life Cycle Analysis (LCA) to standard ISO 14044 available.

No VOC (catalyst)

TECHNICAL INFORMATION

Product Application

Specific machine.

Over dry and clean asphalt.

Maximum humidity : 80%. Application surface temperature $5^{\circ}\text{C} < T < 40^{\circ}\text{C}$.

Cleaning: Solvécol or Solvéo.

For detailed application, refer to Echoflex Application guidance datasheet.

Physical Characteristics

Density: 1.97 to 1.64 kg/L

Dry extract : 85 to 77 %

Packaging and Storage

Packaging: 25 kg - 300 kg

Storage and transport : Dry, frost free place, and away from direct sunlight.

Shelf life : 12 months in unopened packaging (from manufacturing date).

Safety & Environment

Product for professional use only.

Soiled packaging and cleaning products should be discarded according to local regulation.

Refer to Safety data sheet (MSDS) on sar.fr.

Contact our Customer Service on sar.fr

