



# PRIMAFLEX

## ADHESIVE VANISH

Adhesive primer for :

Acrylic Paints  
Coldpastics

## BENEFITS

### Product Characteristics

PRIMAFLEX is a very fluid primer based on modified acrylic resins favoring the adhesion of paints or coldplastics on difficult supports:

- Formula very fluid
- Optimized wetting of the support thanks to its high solvent content
- Useful when paints or coldplastics do not have sufficient adhesion to the support

PRIMAFLEX improves grip but does not guarantee systematic adhesion, in particular on smoothed supports or certain concrete supports. It should not be used on new asphalt substrates because its solvent content would tend to dissolve the substrate.

PRIMAFLEX is not a road marking product. It is not certified NF Road Equipment

### A marking material combining performance and sustainable development.

- Very low dosage product
- Life Cycle Analysis (LCA) according to ISO 14044 standard available.

## TECHNICAL INFORMATION

### Product Application

- Airless machine or manual application
- Over any dry and clean asphalt or old coldplastics markings.
- Maximum humidity : 80%. Application surface temperature  $5^{\circ}\text{C} < T < 45^{\circ}\text{C}$ .
- For detailed application, refer to Thermoplastic Application guidance datasheet.
- Cleaning with solvent. : Solvécol ou Solvéo.

### Physical Characteristics

- Density : de 0,89 à 0,99 kg/l / Dry extract : 30 %
- Dosage : 0.2 to 0.4 litre/m<sup>2</sup> (i.e. 2.5 to 5 m<sup>2</sup>/litre) depending on the substrate.

### Packaging and Storage

- Packaging: 20L.
- Storage and transport : Dry, frost free place, and away from direct sunlight.
- Shelf life : 36 months in unopened packaging (from manufacturing date).

### Safety & Environment

- Product for professional use only.
- Soiled packaging and cleaning products should be discarded according to local regulation.
- Refer to the Safety Datasheet (MSDS) on [www.sar.fr](http://www.sar.fr)

**Contact our Customer Service on**

[serviceclients@sar.fr](mailto:serviceclients@sar.fr)

