



VARNIGUARD

Protective varnish for road markings

BENEFITS

Product Characteristics

VARNIGUARD is a single-component solvent-based protective varnish. It reduces clogging of road markings. The formulation based on acrylic resins allows the widest possible compatibility with other chemistries used in road marking.

- Low dosage for economical use
- Ultra fast dries

VARNIGUARD should never be used on Alkyd paints.

It can be used in premix with road paint, this technique modifying the solvent balance will lead to an extension of the dry time of the modified paint. Translucent, it increases the brilliance of the markings and does not yellow.

A marking material combining performance and sustainable development.

- Life Cycle Analysis (LCA) to standard ISO 14044 available.
- Limited VOC impact due to low levels of dosage.

TECHNICAL INFORMATION

Product Application

- Airless machine or manual application.
- Over any dry and clean new asphalt.
- Maximum humidity : 80%.
- Surface temperature : $5^{\circ}\text{C} < T < 40^{\circ}\text{C}$.
- Cleaning with solvent : Solvécol ou Solvéo.

Physical Characteristics

- Density : 1,08 kg/L
- Dosage : 0.2 to 0.3 litre/m² (i.e. 3.5 to 5 m²/litre), depending on the substrate.

Packaging and Storage

- 20 l
- Storage & Transport : Dry, frost free place.
- Shelf Life : 36 months in unopened packaging from manufacturing date.

Safety & Environment

- Product for professional use only.
- Soiled packaging and cleaning products should be discarded according to local regulation.
- Refer to the Safety Datasheet (MSDS) on www.sar.fr.

Contact our Commercial Service

customerservice@sar.fr

